

PIONEER

Fast Potato and Carrot Peeler



QUICKNESS AND HIGH QUALITY PROCESSING WITH MINIMAL WASTE

Quickness and high quality processing combined with savings may seem impossible, but not for Pioneer, the peeler that peels potatoes and carrots in just two minutes, perfectly and with minimal waste. The specific shape of the peeling disc and the peeling chamber ensure a uniform abrasive action across the whole surface of the product, reducing wastes.

Furthermore an electronic timer controls the peeling time so that potatoes spend no longer than necessary under the abrasive effect. Skins are removed by a jet of water and collected in a filter prior to discharge.

Peeling disc and filter are easily removable for cleaning. This guaranteed hygiene, together with its fast and reliable working, make Pioneer a machine no modern kitchens should work without.

Wilma

LA SCIENZA DELLE GRANDI CUCINE



PIONEER

Fast Potato and Carrot Peeler

TECHNICAL DATA	PIONEER K/15	PIONEER K/30
Loading capacity	15 kg	30 kg
Average peeling time	2 minutes	2 minutes
Water inlet Ø	3/4"	3/4"
Water drain Ø	2"	2"
Gearmotor power	0,55 kW	1,1 kW
Voltage	3~230/400V 50Hz + E	3~230/400V 50Hz + E
Net weight	62 kg	97 kg
Dimensions	mm 650x500x1030 h	mm 750x590x1110 h
K15/T Dimensions	mm 650x500x1220 h	
K30/T Dimensions		mm 750x590x1300 h

SPECIFICATIONS

- Frame and peeling chamber made of AISI 304 stainless steel.
- Peeling disc, made of abrasive-coated Anticorodal, manually removable for cleaning.
- Lid made of robust plastic and equipped with hinge and lock.
- Safety devices on lid and product outfeed.
- Peeling disc powered by a gearmotor with overload cut-out.
- Wall-mounted control panel.
- 24V low voltage controls.

OPTIONS

VEGETABLE CLEANING TABLE

Wall-mounted table made of AISI 304 stainless steel with two work places provided with: potato vat, non-toxic plastic cutting surface with drainage hole, waste bin, water tap and overflow.

Table dimensions: mm 1600x700x850 h.

In versions combined with the vegetable cleaning table, Pioneer K15/T and K30/T are 190 mm taller and may be installed on the right or left sides of the table.



PEEL COLLECTION FILTER



Filter made of AISI 304 stainless steel featuring a container and a removable perforated tank to trap peeling residues.

WATER INLET SOLENOID VALVE

Controlled by the timer, it turns on the supply of water only when the appliance is in operation.

POTATO COLLECTION TROLLEY

Made of AISI 304 stainless steel and equipped with a handle, four wheels and a 2/1 GN container (h: 200 mm). Dimensions: mm 690x660x700 h.



APPLIANCE CONSTRUCTED TO HARMONISED STANDARDS AND COMPLETE WITH CE MARKING

Company with EN ISO 9001 certified Quality Management System